

Asphalt Analyzer YOU! Touch

EN 12697/1 - ASTM D8159-2018 - AASHTO for extraction and determination of binder content using non-flammable solvents.

With the further development of the Asphalt Analyzer YOU, you can control the extraction even more intuitively via the touch display.

What has changed?

- ► Two maintenance windows in the recovery cover
- ► Direct connection to the rotary evaporator
- ► Temperature limiters above recovery cover
- ► Additional inlet sieve in the recovery system for catching of very light asphalt components
- ► The use of the new 2.5 kg washing drum
- ► Use of the 2.5 kg or 3.5 kg washing drum possible

What has remained the same?

- ► Use of ultrasonic sensor in the washing chamber
- ► Preselectable number of washing cycles and drying
- ► Closed solvent cycle
- Automatic drying of minerals and filler
- ► Processing time of at least 40 min.
- ► Reduced environmental impact
- ► Solvent loss < 20ml per extraction

Technical Data

Dimensions appr.	1290 x 800 x 1400 mm
Electrical Data	3/N/PE, 400 V, 50 Hz, 7 kW
Weight	ca. 254 kg
Producer	infraTest Prüftechnik (DE)
Customs Tariff Number	90318080

20-11320

ACCESSOIRES

Washing Drum 2.5 kg



20-1113

Closing Lid



20-1106

Rack Flasks for Glass Test Cup **RTFOT**



20-1100E265

Washing Drum 3,5 kg



0.063 mm

20-1112

0.075 mm

20-1111

Centrifuge Cup



120 mm

20-0330

120 mm/300 g

20-0335





Tel.: +49 (0) 7135-95 00-0 Fax: +49 (0) 7135-95 00-20

info@infraTest.net www.infraTest.net

in You infratest.net/social

